

Lift rolling door let in
Guard $\frac{1}{8}'' \times \frac{1}{16}''$ (4.5 x 4.0 mm)

Lock Side
Screw: $\frac{3}{16}'' \times 2\frac{3}{8}''$
(4 x 60)
+ underplate
+ M5 screw

Goll Gasket A 9020-SC Goll

Handle
+ underplate
+ M5 screw

Gasket"A" Si PDP B0040-099010

Gasket"B" Schlege QL 3004

Lock + Wheels Security: $M5 \times \frac{1}{2}''$
(Schloss + Laufwagen Sicherung $M5 \times 13$ mm)

Trolly Wheels: $\frac{3}{16}'' \times 1\frac{3}{4}''$
(Laufwagen Sicherung 4 x 45 mm)

Screw: $\frac{3}{16}'' \times 1\frac{3}{4}''$ (4 x 45 mm)
Screw: $M5 \times \frac{1}{2}''$ ($M5 \times 13$ mm)

Screw: $\frac{3}{16}'' \times 2\frac{3}{8}''$ (5 x 60)

Lift rolling door Guard
 $\frac{1}{8}'' \times \frac{1}{16}''$ (HST Führung
3.5 x 2.0 mm)

Spacer
Wheels
 $\frac{1}{8}'' \times \frac{1}{16}''$
(3.5 x 2.0)

Gasket"A" Si PDP B0040-099010
Hose Gasket Deventer S 9608

Separating Agent
(Trennmittel König)

Gasket"B" Schlege QL 3004

Foam tape 1-4 $\frac{3}{8}''$
(Kompriband 1-4 10 mm)
Gasket"A" Si PDP B0040-099010

Gasket"A" Si PDP B0040-099010
Foam tape 1-4 $\frac{3}{8}''$ (Kompriband 1-4 10 mm)
Spax SK $\frac{1}{4}'' \times 5\frac{1}{2}''$ (6 x 140)
Separating Agent (Trennmittel König)
Strip $\frac{9}{16}'' \times 1\frac{5}{8}''$ (15 x 42)
Foam tape 1-4 $\frac{3}{8}''$ (Kompriband 1-4 10 mm)
Gluing

Kaya Plywood $2\frac{3}{16}''$ (56 mm)